


■Features

- High Lumen LEDs
- 5mm Bullet Standard Directivity
- UV Resistant Epoxy
- Water Clear Type

■Applications

- Electronic Signs And Signals
- Small Area Illuminations
- Back Lighting/ Other Lighting

■Outline Dimension




■Absolute Maximum Rating

(Ta=25°C)

Item	Symbol	Value		Unit
		W/B/PG	Y/O/R	
DC Forward Current	I _F	30	30	mA
Pulse Forward Current#	I _{FP}	100	100	mA
Reverse Voltage	V _R	5	5	V
Power Dissipation	P _D	102	78	mW
Operating Temperature	T _{opr}	-30 ~ +85		°C
Storage Temperature	T _{stg}	-40 ~ +100		°C
Lead Soldering Temperature	T _{sol}	260°C/5sec		-

■Directivity



#Pulse width Max.10ms Duty ratio max 1/10

■Electrical -Optical Characteristics

(Ta=25°C)

Part Number	Color			V _F (V)*			I _R (μA)	Φ _V (LM)*			I _v (mcd)*			Wd(nm)*			2θ1/2(deg)
				Min.	Typ.	Max.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.	Typ.
				I _F =30mA			V _R =5V	I _F =30mA			I _F =30mA			I _F =30mA			
OSW44P5201A	Pure White	W		-	2.9	3.4	10	8.5	10	-	60000	72000	-	5500-8500K(X:0.31,Y:0.33)			8
OSM54P5201A	Warm White	M		-	2.9	3.4	10	8.5	10	-	60000	72000	-	2700-3200K(X:0.44,Y:0.41)			8
OSB56P5201A	Blue	B		-	2.9	3.4	10	2.5	3.0	-	25000	30000	-	465	470	475	8
OSG5GP5201A	Pure Green	PG		-	2.9	3.4	10	8.5	10	-	60000	72000	-	520	525	530	8
OS5YKP5201A	Yellow	Y		-	2.1	2.6	10	3.5	4.5	-	43000	50000	-	585	590	595	8
OS5OKP5201A	Orange	O		-	2.1	2.6	10	3.5	4.5	-	43000	50000	-	600	605	610	8
OS5RKP5201A	Red	R		-	2.1	2.6	10	3.5	4.5	-	43000	50000	-	620	625	630	8

*1 Tolerance of measurements of chromaticity coordinate is ±10%

*2 Tolerance of measurements of dominant wavelength is ±1nm

*3 Tolerance of measurements of luminous flux is ±15%

*4 Tolerance of measurements of forward voltage is ±0.1V

LED & Application Technologies

